



www.vertextrading.es

C
O
L
E
C
C
I
O
N
T

COMPOSICIÓN / COMPOSITION:	100% PES
ANCHO / WIDTH:	140 cm.
PESO / WEIGHT (+/- 5%):	360 gr/m ² - 500 gr/ml
RESISTENCIA DE ROTURA AL RASGADO: TEAR STRENGTH URDIMBRE / WARP:	3'5 mm BS-3320:1998
TRAMA / WEFT:	3,5 mm BS-2543:1995
RESISTENCIA A LA ABRASIÓN: ABRASION RESISTANCE CICLOS / MARTINDALE:	>30.000 ISO 12947-2: 1998
SOLIDEZ DE LOS COLORES A LA LUZ: COLOUR FASTNESS TO LIGHT	4-5 UNE 40187 / BS 1006-B02
SOLIDEZ A LA LIMPIEZA EN SECO: RUBBING SOLVENTS	4-5 ISO 105D01
SOLIDEZ DE LOS COLORES AL LAVADO: RUBBING FASTNESS IN HUMID STATE	4-5 ISO 105D01
RESISTENCIA AL PILLING: PILLING RESISTANCE	4-5 ISO/DIS 12945-1



INSTALIMP[®]
TREATMENT

HIDROFUGADO
ANTIMANCHAS